



BUILT TO PERFORM

| TECHNICAL SPECIFICATIONS | | BTX 5000 | |
|--------------------------------|-------------------------------------|---------------------------|--------------------------------------|
| Engine | | Dimensions Carrier | |
| Type | Deutz | Length | 344in |
| Model | F6L914W air cooled | Width | 96in |
| Cylinders | In-Line 6 | Height | 94in |
| Exhaust | Exhaust Purifier | | |
| Electrical | 24 volt | Performance | |
| | | 1st Gear | 3 km/h |
| Powertrain Transmission | | 2nd Gear | 7 km/h |
| Transmission | Clark Hurth | 3rd Gear | 22 km/h |
| Series | T20000 | | |
| Gears forward | Three (3) | Weight | |
| Gears reverse | Three (3) | Net | 31,000lbs |
| 4 wheel drive | Yes | | |
| | | Carrier | |
| Axles | | Rops/Fops | Yes |
| Planetary Type | Yes | Passenger seat | Yes |
| Rear | Fixed | Fire Suppression | Yes |
| Front | Oscillation | Lockable Master | Yes |
| | | Safe Entry/exit 3 point | Yes |
| Brakes | | | |
| Service | 4 Wheel Wet Disc | Additional Options | |
| Emergency | 4 Wheel Wet Disc+Wet disc driveline | Engine | Mercedez 904 Water Cooled (147hp) |
| Park | 4 Wheel Wet Disc+Wet disc driveline | Enclosed Cab | A/C or heat |
| | | LED lights | 24 volts |
| Boom and Deck | | Lubrication system | Lincoln |
| Boom | Hi ab 090 | Tool Compartment | Custom built |
| Deck capacity | Up To 28000lbs | Fast Fuel System | Wiggins |
| Deck size | 8 feet wide x 12 feet long | Compressor | Hydraulic driven |
| Hydraulic Tailgate | Optional | Spare tire and rim | 1200 x 20 |
| Stabilizers | Hydraulic | Power Pack | Air over hydraulic |
| Remote | Optional | Custom | Other custom-built options available |

At JS Manufacturing, engineering is a process of continuous improvement: therefore, specifications are subject to change without notice.

BOOM TRUCK

