



BUILT TO PERFORM

TECHNICAL SPECIFICATIONS		BTX 4100	
Engine		Dimensions Carrier	
Type	Deutz	Length	384in
Model	D914L04 air cooled	Width	96in
Cylinders	6 cyl	Height	93in
Exhaust	Exhaust Purifier		
Electrical	24 volt	Performance	
		1st Gear	3 km/h
Powertrain Transmission		2nd Gear	7 km/h
Transmission	Clark Hurth	3rd Gear	22 km/h
Series	T20000		
Gears forward	Three (3)	Weight	
Gears reverse	Three (3)	Net	28,000lbs
4 wheel drive	Yes		
		Carrier	
Axles	Dana 123	Rops/Fops	Yes
Planetary Type	Yes	Passenger seat	N/A
Rear	Fixed	Fire Suppresion	Yes
Front	Oscillation	Lockable Master	Yes
		Safe Entry/exit 3 point	Yes
Brakes		Additional Options	
Service	4 Wheel Wet Disc	Engine	Mercedes 904, Mercedes 906, Cat 4.4, Cummins QSB3.3, Deutz 4 cyl
Emergency	4 Wheel Wet Disc+Wet disc driveline	Enclosed Cab	A/C or heat
Park	4 Wheel Wet Disc+Wet disc driveline	LED lights	24 volts
Boom and Deck		Lubrication system	Lincoln
Boom	Hi ab 090	Tool Compartement	Custom built
Deck Capacity	Up to 28000lbs	Fast Fuel System	Wiggins
Deck size	8 feet wide x 12 feet long	Compressor	Hydraulic driven
Hydraulic Tailgate	Optional	Spare tire and rim	9x 20
Stabilizers	Hydraulic	Power Pack	Air over hydraulic
Remote	Optional	Custom	Other custom-built options available

